

IPC-K22A

2MP IR Network Camera



- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- Outputs max. 2MP (1920 × 1080) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Max. IR distance: 10 m
- Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Alarm: 1 in, 1 out; 256 G SD card, built-in Mic and speaker
- Supports 256 G Micro SD card
- 12V DC/PoE power supply, easy for installation
- Supports PIR



Series Overview

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry series network camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

Functions

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

WDR

With advanced Wide Dynamic Range (WDR) technology, Dahua network camera provides clear details in the environment of strong brightness contrast. The bright and dark area can get clear video even in high brightness environment or with backlight shadow.

Smart Illumination

Dahua Smart Illumination technology can display image in the environment of low illuminance or completely dark environment. According to the distance of the targets, the camera adjusts illuminations intensity automatically to display the details of the moving target.

Motion Detection

When moving objects appear in the monitoring image, Dahua Motion Detection (General) technology triggers alarm or records.

Day/Night

Dahua Day/Night function provides color image when illumination is adequate; when illuminance is inadequate, it switches night mode and provides white and black image. It can guarantee that the network camera can work normally when illuminance changes.

Voice Call

With built-in high-sensitivity Mic and high-power speaker, the camera can realize voice call through DMSS client.

Entry Series | IPC-K22A

Technical Specification				
Camera				
Image Sensor	1/2.7"2Megapixel progressive CMOS			
Max. Resolution	1920 (H) × 1080 (V)			
ROM	128 MB			
RAM	128 MB			
Scanning System	Progressive			
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s			
Min. Illumination	Manual 1/30 s 0.215 Lux @F2.0 (Color, 80 IRE); 0.232 Lux @F2.0 (W/B, 80 IRE); 0 Lux (IR on) Manual 1/3 s 0.0324 Lux @F2.0 (Color, 80 IRE); 0.0334 Lux @F2.0 (W/B, 80 IRE); 0 Lux (IR on)			
S/N Ratio	>50.6 dB			
Illumination Distance	10 m (32.8 ft) (IR LED)			
Illuminator On/Off Control	Auto			
Illuminator Number	1 (IR LED)			
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–90°			
Lens				
Lens Type	Fixed-focal			
Mount Type	M12			
Focal Length	2.8 mm			
Max. Aperture	F2.0			
Field of View	Horizontal: 102° Vertical: 54° Diagonal: 120°			
Iris Type	Fixed			
Close Focus Distance	0.5 m (1.6 ft)			
DORI Distance	Detect	Observe	Recognize	Identify
	38.6 m (126.6ft)	15.4 m (50.5 ft)	7.7 m (25.3 ft)	3.9 m (12.8 ft)
Video				
Video Compression	H.265; H.264; H.264H; H.264B; MJPEG			
Smart Codec	H.264: Yes H.265: Yes			
Video Frame Rate	50 Hz Main stream (1920 × 1080 @25 fps), sub stream (640 × 480 @25 fps) Main stream (1280 × 960 @25 fps), sub stream (640 × 360 @25 fps) Main stream (1280 × 720 @25 fps), sub stream (320 × 240 @25 fps)			
	60 Hz Main stream (1920 × 1080 @30 fps), sub stream (640 × 480 @30 fps) Main stream (1280 × 960 @30 fps), sub stream (640 × 360 @30 fps) Main stream (1280 × 720 @30 fps), sub stream (320 × 240 @30 fps)			
	720p (1280 × 720 @30 fps), sub stream (640 × 480 @30 fps)			
	720P (1280 × 960 @30 fps), sub stream (640 × 480 @30 fps)			
	720P (1280 × 720 @30 fps), sub stream (320 × 240 @30 fps)			
Stream Capability	2 streams			
Resolution	1080p (1920 × 1080); 1.3M (1280 × 960); 720P (1280 × 720); VGA (640 × 480); QVGA (320 × 240)			
Bit Rate Control	CBR/VBR			
Video Bit Rate	H.264: 184 kbps–6144 kbps H.265: 73 kbps–6144 kbps			
Day/Night	Auto (ICR)/Color/B/W			
BLC	Yes			
HLC	Yes			
WDR	DWDR			
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom			
Gain Control	Auto/Manual			
Noise Reduction	3D DNR			
Motion Detection	OFF/ON (4 areas, rectangular)			
Region of Interest (RoI)	Yes (4 areas)			
Smart Illumination	Yes			
Image Rotation	0°/90°/180°/270°			
Mirror	Yes			
Privacy Masking	4 areas			
Audio				
Built-in MIC	Yes			
Audio Compression	AAC; G.711a; G.711Mu			
Alarm				
Alarm Event	No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; voltage detection; motion detection; video tampering			
Network				
Network	RJ-45 (10/100 Base-T)			
SDK and API	Yes			
Protocol	HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; IPv4/v6; QoS; NTP			
Interoperability	ONVIF (Profile T/Profile S/Profile G); CGI; DMSS			
User/Host	20 (Total bandwidth: 50 M)			
Storage	NAS; FTP; SFTP; Micro SD card (256 G)			
Browser	IE: IE7 and later Chrome: Chrome 45 and later Firefox: FireFox 46 and later Safari: Mac os Safari12			
Management Software	DMSS			
Mobile Phone	IOS; Android			
Certification				
Certification	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B			
Port				
Alarm Input	1 channel in: 5mA 3V–5V DC			
Alarm Output	1 channel out: 300mA 12V DC			

Entry Series | IPC-K22A

Power

Power Supply	12V DC/PoE
Power Consumption	Max 2.9W (12V DC) (IR full intensity)

Environment

Operating Conditions	-10°C to +45°C (14°F to +113°F)/Less than 95%RH
Storage Conditions	-40°C to +60°C (-40°F to +140°F)

Structure

Casing	Plastic
Dimensions	Φ78.5 mm × 90.5 mm × 127.8 mm (3.1" × 3.6" × 5.0") (L × W × H)
Net Weight	170 g (0.4 lb)
Gross Weight	270 g (0.6 lb)

Ordering Information

Type	Model	Description
2MP Camera	DH-IPC-K22AP	2MP IR Network Camera, PAL
	DH-IPC-K22AN	2MP IR Network Camera, NTSC

Dimensions (mm[inch])

