# HIKVISION

Vehicle-Mounted Camera

User Manual

UD09114B-A

# **User Manual**

©2018 Hangzhou Hikvision Digital Technology Co., Ltd. About thisManual

### This manual applies to Vehicle-Mounted Camera.

This Manual is subject to domestic and international copyright protection. Hangzhou Hikvision Digital Technology Co., Ltd. ("Hikvision") reserves all rights to this manual. This manual cannot be reproduced, changed, translated, or distributed, partially or wholly, by any

means, without the prior written permission of Hikvision. **Trademarks** 

### **HIKVISION** and other Hikvision marks are the property of Hikvision and are registered trademarks or the subject of applications for the same by Hikvision and/or its affiliates. Other trademarks mentioned in this

manual are the properties of their respective owners. No right of license is given to use such trademarks without express permission. Disclaimer TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, HIKVISION MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE IMPLIED

WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, REGARDING THIS MANUAL. HIKVISION DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE OF THE MANUAL, OR THE CORRECTNESS, ACCURACY, OR RELIABILITY OF INFORMATION CONTAINED HEREIN. YOUR USE OF THIS MANUAL AND ANY RELIANCE ON THIS MANUAL SHALL BE WHOLLY AT YOUR OWN RISK AND RESPONSIBILITY.

LAW, IN NO EVENT WILL HIKVISION, ITS DIRECTORS, OFFICERS, EMPLOYEES, OR AGENTS BE LIABLE TO YOU FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR INDIRECT DAMAGES, INCLUDING, AMONG OTHERS, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, SECURITY BREACHES, OR LOSS OF DATA

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE

OR DOCUMENTATION, IN CONNECTION WITH THE USE OF OR RELIANCE ON THIS MANUAL, EVEN IF HIKVISION HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OR LIMITATION OF LIABILITY OR CERTAIN DAMAGES, SO SOME OR ALL OF THE ABOVE EXCLUSIONS OR

LIMITATIONS MAY NOT APPLY TO YOU.

Поставщик систем безопасности TELECAMERA.RU

#### Regulatory information **FCCInformation**

#### FCCcompliance: This equipment has been tested and

marked with this symbol cannot be disposed of as unsorted municipal waste in the European Union. For proper recycling,

#### harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a

residential area is likely to cause harmful interference in which case the user will be required to correct the

found to comply with the limits for a digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against

### **FCCConditions**

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference. 2. This device must accept any interference received, including interference that may cause undesired operation

### **EUConformity Statement**

interference at his own expense.



supplied accessories too are marked with "CE" and comply therefore with the

This product and - if applicable - the

applicable harmonized European standards listed under the Low Voltage Directive 2014/35/EC, the EMC Directive 2014/30/EC. 2012/19/EU (WEEE directive): Products



return this product to your local supplier upon the purchase of equivalent new equipment, or

dispose of it at designated collection points. For more information see: www.recyclethis.info.



2006/66/EC (battery directive): This product contains a battery that cannot be disposed of as unsorted municipal waste in

the European Union. See the product documentation for specific battery information. The battery is marked with this symbol, which may include lettering to indicate cadmium (Cd), lead (Pb), or mercury (Hg). For proper recycling, return the battery to your supplier or to a designated collection point. For more information see: www.recyclethis.info.

### Industry Canada ICES-003 Compliance

This device meets the CAN ICES-3 (A)/NMB-3(A) standards requirements.

### Поставщик систем безопасности TELECAMERA.RU Safety instruction

These instructions are intended to ensure that user can use the product correctly to avoid danger or property loss. The precaution measure is divided into "Warnings" and

"Cautions" Warnings: Seriousinjury or death may occur if any of the

warnings are neglected. Cautions:Injuryor equipment damage may occur if any



of the cautions are neglected.

In the use of the product, you must be in strict compliance with the electrical safety regulations of the nation and region.

Refer to technical specifications for detailed information.

Input voltage should meet both the SELV (Safety Extra Low Voltage) and the Limited Power Source with AC 24V or DC 12V according to the IEC60950-1 standard. Refer to technical specifications for detailed

information. Do not connect several devices to one power adapter as adapter overload may cause over-heating or a fire Make sure that the plug is firmly connected to the

power socket. When the product is mounted on wall or ceiling, the device shall be firmly fixed. If smoke, odor or noise rise from the device, turn off the power at once and unplug the power cable, and

then please contact the service center. If the product does not work properly, contact your dealer or the nearest service center. Never attempt to disassemble the camera by yourself. (We shall not assume any responsibility for problems caused by unauthorized repair or maintenance.)



WARNING Make sure the power supply voltage is correct before using the camera.

Do not drop the camera or subject it to physical shock.

Do not touch senor modules with fingers. If cleaning is necessary, use clean cloth with a bit of ethanol and

wipe it gently. If the camera will not be used for an extended period, replace the lens cap to protect the

sensor from dirt. Do not aim the camera at the sun or extra bright places. Blooming or smearing may occur otherwise (which is not a malfunction), and affect the endurance

of sensor at the same time.

Поставщик систем безопасности TELECAMERA.RU

when any laser equipment is in using, make sure that the surface of sensor will not be exposed to the laser heam.

Do not place the camera in extremely hot, cold, dusty or damp locations, and do not expose it to high

electromagnetic radiation.

Поставщик систем безопасности TELECAMERA.RU The sensor may be burned out by a laser beam, so

<ul> <li>To avoid heat accumulation, good ventilation is required for operating environment.</li> <li>Keep the camera away from liquid while in use.</li> <li>While in delivery, the camera shall be packed in its original packing, or packing of the same texture.</li> <li>Symbol Conventions</li> <li>The symbols that may be found in this document are defined as follows.</li> </ul>	
Symbol	Description
NOTE	Provides additional information to emphasize or supplement important points of the main text.
<b>A</b> WARNING	Indicates a potentially hazardous situation, which if not avoided, could result in equipment damage, data loss, performance degradation, or unexpected results.
DANGER	Indicates a hazard with a high level of risk, which if not avoided, will result in





death or serious injury.





This series of camera adopts new generation sensor with high sensitivity and advanced circuit design technology. It features high resolution, low image distortion and low

# 1 Introduction

1.1 Product Features

noise, etc., which makes it suitable for surveillance system and image processing system. The main features are as follows: High performance CMOS sensor and high resolution bring high-quality image.

AGC (Auto Gain Control). Aviation plug output, shock proof. IP68

# 1.2 Overview

#### 1.2.1 Overview of Vehicle-Mounted Camera

The overview of the camera is shown below.




Figure 1-1 Overview

#### 1.2.2 Aviation Plug Interfaces

There are 2 types for the aviation plug interfaces, as shown in below.




Figure 1-2 Interfaces of Aviation Plug

### 2 Installation

#### Before you start:

Make sure that all the related equipment is power-off during the installation. Check the specification of the products for the

Check whether the power supply is matched with your

included.

by yourself.

installation environment

the camera and the mounting.

Поставщик систем безопасности TELECAMERA.RU Please make sure that the device in the package is in good condition and all the assembly parts are

M 2 5 x 7

- Align the holes on the bracket with the installation holes on the drill template.
  - Use 3 crews (PA4 x 25) to secure the bracket to the 5. template.
    - Holes for Fixing Bracket

Figure 2-3 Secure Bracket

- Figure 2-2 Loosen Screws
- Figure 2-1 Drill Template 3. Loosen 4 crews (M2.5 x 7) on the cover.

Drill the screw holes according to the drill 2. template.

Do not pull and drag the camera cables hard.

Steps: 1. Paste the drill template to the vehicle wall.

power output to avoid damage. Be sure that there is enough space to install the camera and accessories. Make sure the part, which is used to install the camera, is strong enough to withstand four times the weight of

If the product does not function properly, please contact your dealer or the nearest service center. Do not disassemble the camera for repair or maintenance

#### Поставщик систем безопасности TELECAMERA.RU Route camera's cables through the cable hole of

the bracket.




Secure the seal ring near the cable hole.

8. Adjust the camera main body with UP upward as


7

the figure below.



(Optional) If the installation site of the camera

- needs to be sealed, please wipe silicagel on the screw position and the cable hole, and seal them.
- 10. Align the cover with the crew holes on the bracket, and insert 4 set crews (M2.5 x 7).



- 11. Connect the camera's cables to the corresponding 4-pin aviation plug.
- 12. Adjust the camera according to the figure below to get an optimum angle, and fasten 4 set crews (M2.5 x 7).




Figure 2-7 Tighten Screws and Adjust Camera 13. Tear the protective film on the lens off.