

DH-HAC-D3A21-Z

2MP HDCVI IR Dome Camera



- Max 30fps@1080P
- CVI/CVBS/AHD/TVI switchable
- 2.7-12mm motorized lens
- Max. IR length 30m, Smart IR
- IP67, DC12V



System Overview

Experience 1080P full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 1080P HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 800m(1080p)/1200m(720P) transmission via coaxial cable, and up to 300m(1080P)/450m(720P) via UTP cable.*

*This function is available for select models.

Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -30 °C to +60 °C (-22 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Cooper Series | DH-HAC-D3A21-Z

Technical Specification

Camera	
Image Sensor	1/2.7 inch CMOS
Effective Pixels	1920(H)×1080(V), 2MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25s–1/100000s NTSC: 1/30s–1/100000s
S/N Ratio	>65dB
Minimum Illumination	0.04Lux/F1.7, 30IRE, 0Lux IR on
Fill Light Working Distance	30 m (98.4 ft)
IR On/Off Control	Auto; manual
IR LED Number	2
Pan/Tilt/Rotation Range	Pan: 0°–355° Tilt: 0°–75° Rotation: 0°–355°

Lens					
Lens Type		Motorized vari-focal			
Auto Focus		N/A			
Mount Type		φ14			
Focal Length		2.7 mm-12 mm			
Max. Aperture		F1.7			
Field of View		Diagonal: 38°– 125° Horizontal: 33°–102° Vertical: 19°– 53°			
Iris Type		Fixed iris			
Close Focus Distance		1.2 m (3.9 ft)			
DORI Distance		Detect	Observe	Recognize	Identify
	2.7mm	48.3m (158.5ft)	19.3 m (63.3 ft)	9.7 m (31.8 ft)	4.8 m (15.7ft)
	12mm	131 m (429.8 ft)	52.4 m (171.9 ft)	26.2 m (86.0 ft)	13.1 m (43.0 ft)

Video	
Frame Rate	CVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; AHD: 1080P@25/30fps; 720P@25/30fps; TVI: 1080P@25/30fps; 720P@25/30fps; 720P@50/60fps; CVBS: 960H
Resolution	1080P (1920×1080); 720P (1280×720); 960H (960×576/960×480)
Day/Night	Auto switch by ICR
BLC	BLC/HLC/DWDR
WDR	DWDR
White Balance	Auto; manual
Gain Control	Auto; manual
Noise Reduction	2D NR
Smart IR	Yes

Electronic Defog	Yes
Mirror	Off/On
Privacy Masking	Off/On (8 area, rectangle)

Certifications	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)
----------------	--

Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port

Power	
Power Supply	12V ±30% DC
Power Consumption	Max 5.28W (12V DC, IR on)

Environment	
Operating Temperature	-30°C to +60°C (-22°F to 140°F);<95% (non-condensation)
Storage Temperature	-30°C to +60°C (-22°F to 140°F);<95% (non-condensation)
Protection Grade	IP67

Structure	
Casing	Plastic throughout the whole casing
Camera Dimensions	Φ122.0 mm × 98.1 mm (Φ4.80" × 3.86")
Net Weight	0.34 kg (0.75 lb)
Gross Weight	0.46 kg (1.01 lb)

Ordering Information

Type	Part Number	Description
2MP Camera	DH-HAC-D3A21P-Z 2.7-12mm	2MP HDCVI IR Dome Camera
	DH-HAC-D3A21N-Z 2.7-12mm	
Accessories	PFA137	Junction box (For use alone)
	PFA123	IP66 Junction box
	PFB203W	Wall Mount Bracket (For use alone or with PFA152-E)
	PFA152-E	Pole Mount Bracket (For use with PFB203W)
	PFA200W	Rain Shade (For use with PFA137 wall mount)
	PFA106	Mount Adapter (For use with PFB220C)
	PFB220C	Ceiling Mount Bracket (For use with PFA106)
	PFM321D	12V 1A Power Adapter
	PFM904	Integrated Mount Tester
	PFM800-E	Passive Video Balun
	PFM820	UTC Controller

Cooper Series | DH-HAC-D3A21-Z

Accessories

Optional:



PFA137
Junction box (For use
alone)



PFA123
IP66 Junction box



PFB203W
Wall Mount Bracket
(For use alone or with
PFA152-E)



PFA152-E
Pole Mount Bracket (For
use with PFB203W)



PFA200W
Rain Shade (For use with
PFA137 wall mount)



PFA106
Mount Adapter (For
use with PFB220C)



PFB220C
Ceiling Mount Bracket
(For use with PFA106)



PFM321D
12V 1A Power Adapter



PFM904
Integrated Mount Tester





PFM800-E
Passive HDCVI Balun



PFM820
UTC Controller

Dimensions (mm[inch])



Junction Mount	Wall Mount	Ceiling Mount
Pole Mount(Vertical)		