

# KR Series Wiegand Readers



KR100 E/M



KR101 E/M



KR300 E/M



KR200 E/M



KR102 E/M



KR202 E/M



KR201 E/M

## Product Description

The KR Series is the main accessories line of external wiegand readers for all our access control devices. With an elegant and robust design, they are easy to connect and install, and offer the possibility to control one door from both sides. The LED lights indicate allowed or denied access. They have a proximity reading range of up to 10cm in the E series case and up to 5cm in the M series case. The fact that this series is waterproof, and the operating temperatures can range from -20° to +65°, it is the ideal solution for outdoor installation. Also they can be connected with our C3 controllers.

## Features

- ✓ Easy to install
- ✓ 125KHz Proximity/13.56MHz Mifare Card Reader
- ✓ Read Range: Up to 10CM(125KHz)/5CM(13.56MHz)
- ✓ 26/34bit Wiegand (default)
- ✓ Easy to install on Metal Door Frame or Mullion
- ✓ External LED Control
- ✓ External Buzzer Control
- ✓ Indoor / Outdoor Operation
- ✓ Solid Epoxy Injection
- ✓ Waterproof IP65
- ✓ Reverse Polarity Protection
- ✓ Elegant and robust design




# KR Series Wiegand Readers



## Specifications

Model	KR100E/M	KR101E/M	KR102E/M	KR200E/M	KR201E/M	KR202E/M	KR300
<b>Read Range</b>	KR100E Up to 10 CM KR100M Up to 5 CM	KR101E Up to 10 CM KR101M Up to 5 CM	KR2102E Up to 10 CM KR102M Up to 5 CM	KR200E Up to 10 CM KR200M Up to 5 CM	KR201E Up to 10 CM KR201M Up to 5 CM	KR202E Up to 10 CM KR202M Up to 5 CM	Up to 10CM
<b>Reading time ( Card )</b>	≤ 300 ms	≤300ms	≤300ms	≤300ms	≤300ms	≤300ms	≤300ms
<b>Power</b>	DC 6-14V / Max.70mA	DC 6-14V / Max.70mA	DC 6-14V / Max.70mA	DC 6-14V / Max.70mA	DC 6-14V / Max.70mA	DC 6-14V / Max.70mA	DC 6-14V / Max.70mA
<b>Input Port</b>	2ea (External LED Control, External Buzzer Control)	2ea (External LED Control, External Buzzer Control)	2ea (External LED Control, External Buzzer Control)	2ea (External LED Control, External Buzzer Control)	2ea (External LED Control, External Buzzer Control)	2ea (External LED Control, External Buzzer Control)	2ea (External LED Control, External Buzzer Control)
<b>Output Card Format</b>	26bit Wiegand (E) 34bit Wiegand (M)	26bit Wiegand (E) 34bit Wiegand (M)	26bit Wiegand (E) 34bit Wiegand (M)	26bit Wiegand (E) 34bit Wiegand (M)	26bit Wiegand (E) 34bit Wiegand (M)	26bit Wiegand (E) 34bit Wiegand (M)	26bit Wiegand (E) 34bit Wiegand (M)
<b>Output Pin Format</b>	8 bits			8 bits			
<b>LED indicator</b>	2 Color LED Indicators (Red and Green)	2 Color LED Indicators (Red and Green)	2 Color LED Indicators (Red and Green)	2 Color LED Indicators (Red and Green)	2 Color LED Indicators (Red and Green)	2 Color LED Indicators (Red and Green)	2 Color LED Indicators (Red and Green)
<b>Beeper</b>	yes	yes	yes	yes	yes	yes	yes
<b>Operating temperature</b>	"-20° to +65°C"	"-20° to +65°C"	"-20° to +65°C"	"-20° to +65°C"	"-20° to +65°C"	"-20° to +65°C"	"-10° to +70°C"
<b>Operating Humidity</b>	10% to 90% (relative humidity non-considered)	10% to 90% (relative humidity non-considered)	10% to 90% (relative humidity non-considered)	10% to 90% (relative humidity non-considered)	10% to 90% (relative humidity non-considered)	10% to 90% (relative humidity non-considered)	10% to 90% (relative humidity non-considered)
<b>Color</b>	Black	Black	Black	Black	Black	Black	Black
<b>Material</b>	ABS+PC with texture	ABS+PC with texture	ABS+PC with texture	ABS+PC with texture	ABS+PC with texture	ABS+PC with texture	ABS+PC with texture
<b>Dimension: (WxHxT) mm</b>	116x75x17.3	77.5x42.8x16.5	86x86x16.3	86x86x16.8	84.5x44x16.8	87x86x22.4	77.5x42.8x16.5
<b>Weight</b>	120g	50g	120g	110g	55g	126g	50g
<b>Index of Protection</b>	IP65	IP65	IP64	IP65	IP65	IP64	IP65

## Connectivity diagram



ZKTeco Inc.  
ZK Mansion, Wuhe Rd, Gangtou, Bantian, Buji Town,  
Longgang District, Shenzhen China 518129  
Tel: 86-755-8960 2345/46/47/48  
E-mail: sales@zkteco.com  
www.zkteco.com

Global Offices:  
USA: +1 732-412-6007  
EU: +34 916532891  
Brazil: +55 31 2515-8326  
Thailand: +66-027199154  
Mexico: +52-55-52928418

South Africa: +27 12 259 1047  
Egypt: +201110444134  
Dubai: +971 4 6091 310  
India: +91 8123536788  
Indonesia: +62 21 2921 8949

Vietnam: +84-0169-5813007  
Philippines: +63 9084118832  
Russia: +8 915 178-46-81

sales@zkteco.eu