

# Tiandy



## TC-D343 Spec:MON/P/V2.0

## 43-inch Plastic LED Monitor



### KEY FEATURES

- Size: 43 inches
- Resolution: 1920\*1080
- Ratio: 16:9
- Backlight: LED
- Brightness:  $\geq 250\text{cd/m}^2$
- Field of view: 178°
- Interface: HDMI\*1, VGA\*1, USB\*1
- Material: plastic
- Standard speaker, HDMI cable, base or stand, remote control
- MTBF  $\geq 30000$  hours



## SPECIFICATIONS

<b>Panel type</b>	IPS
<b>Panel size</b>	43"
<b>Aspect ratio</b>	16:9
<b>Gauge(mm)</b>	0.49005*0.49005
<b>Resolution</b>	1920×1080
<b>Luminance(cd/m<sup>2</sup>)</b>	300
<b>Contrast</b>	1000:1
<b>Response time(ms)</b>	8
<b>Refresh rate</b>	60HZ
<b>Colouration</b>	70%NTSC
<b>Display size(mm)</b>	940.896(H)×529.254(V)
<b>Viewpoint(H/V)</b>	178 °(H)/ 178 °(V)
<b>Video input</b>	1*HDMI +1*VGA+1*USB
<b>Video output</b>	N/A
<b>Audio input</b>	N/A
<b>Audio output</b>	Speaker*2+Audio in
<b>Control interface</b>	N/A
<b>Speaker</b>	8Ω10W
<b>OSD(Language)</b>	13,countries (English,French,Spanish,Portuguese,German,Italian,Dutch,Swedish,Finnish,Polish, Czech,Russian,Simplified Chinese)
<b>Wall mounting holes (mm)</b>	200*200
<b>Wall mounted threads</b>	M6(Thread Depth 10mm)
<b>Input Voltage</b>	100 V ~ 240 V, 50-60 Hz
<b>Typical power consumption(W)</b>	≤90
<b>Standby power consumption(W)</b>	≤0.5
<b>Operating temperature</b>	0°C ~ 40°C
<b>Operating humidity</b>	10% ~ 80% RH Non-Condensing
<b>Storage humidity</b>	10% ~ 90% RH Non-Condensing
<b>Bare metal size(mm)</b>	955.2(W)*206.9(D)*605.3(H)
<b>Package Size(mm)</b>	1055(W)*141(D)*645(H)
<b>Net weight(Kg)</b>	6.1
<b>Gross weight(Kg)</b>	11.4

# Tiandy

## DIMENSIONS (Unit: mm)

