

Tiandy



TC-D350 Spec:MON/4K/P/V2.0 50-inch Plastic LED Monitor



KEY FEATURES

- Size: 50 inches
- Resolution: 3840*2160
- Ratio: 16:9
- Backlight: LED
- Brightness: $\geq 250\text{cd/m}^2$
- Field of view: 178°
- Interface: HDMI*2, DP*2, Audio out*1
- Material: plastic
- Standard speaker, HDMI cable, base or stand, remote control
- MTBF ≥ 30000 hours



SPECIFICATIONS

| | |
|-------------------------------------|--|
| Panel type | VA |
| Panel size | 50" |
| Aspect ratio | 16:9 |
| Gauge(mm) | 0.285375x0.285375 |
| Resolution | 3840×2160 |
| Luminance(cd/m²) | 300 |
| Contrast | 5000:1 |
| Response time(ms) | 9.5 |
| Refresh rate | 60HZ |
| Colouration | 70%NTSC |
| Display size(mm) | 1105.84(W) x 669.41(H) |
| Viewpoint(H/V) | 178 °(H) / 178 °(V) |
| Video input | 2*HDMI+2*DP |
| Video output | N/A |
| Audio input | N/A |
| Audio output | Speaker*2+Audio out |
| Control interface | N/A |
| Speaker | 8Ω10W |
| OSD(Language) | 16,countries (English,French,Spanish,Portuguese,German,Italian,Dutch,Swedish,Finnish,Polish,Czech,Russian,Korean,Simplified,Chinese,Traditional,Chinese,Japanese) |
| Wall mounting holes (mm) | 200*200mm |
| Wall mounted threads | M6(Thread Depth 10mm) |
| Input Voltage | 100 V ~ 240 V, 50-60 Hz |
| Typical power consumption(W) | ≤120 |
| Standby power consumption(W) | ≤0.5 |
| Operating temperature | 0°C ~ 40°C |
| Operating humidity | 20% ~ 85% RH Non-Condensing |
| Storage humidity | 10% ~ 90% RH Non-Condensing |
| Bare metal size(mm) | 1111.2(W)*77.4(D)*704.9(H) |
| Package Size(mm) | 1200(W)*141(D)*725(H) |
| Net weight(Kg) | 8.5 |
| Gross weight(Kg) | 10.5 |

Tiandy

DIMENSIONS (Unit: mm)

