

PFS3008-8ET-60



PFS3008-8ET-60

8-Port Fast Ethernet PoE Switch with 4-Port PoE



Features

- Layer two commercial switch
- Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards
- MAC auto learning, aging, MAC address capacity is 2K
- Supports MDI/MDIX self-adaptation
- RJ45 port supports 10/100 Mbps self-adaptation
- Supports IEEE802.3af and IEEE802.3at power supply standards
- Adopts metal enclosure
- Supports Hi-PoE 60W
- Supports DC 48-57V power supply

Product Overview

PFS3008-8ET-60 is a 8-port fast Ethernet switch, which supports 250 meters long distance PoE transmission. It provides 4*10/100Mbps PoE ports and 4*100 Mbps Ethernet ports. The product is equipped with two transmission modes (Default/Extend), which are controlled by DIP switch.

Technical Specification

Model	PFS3008-8ET-60
Ethernet Port	4*10/100 Mbps PoE ports 4*10/100Mbps ports
PoE Power Consumption	Port1≤60W, Port2-4≤30W, Totals60W
PoE Protocol	IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE
Switching Capacity	1.8Gbps
Packet Forwarding Rate	1.19Mpps
Packet Buffer Memory	768Kb
MAC Table Size	2K
Flow Control	Enable by default
Application Humidity	10%~90%
Power	DC48~57V power adapter
Lightning Protection	Common Mode 2KV Differential Mode 0.5KV
Working Temperature	-10°C~+55°C
Weight	0.48kg
Dimension(W×D×H)	190mm×100mm×30mm