

# KR600 Series



KR600-E/M



KR601-E/M



KR602-E/M

## RFID/Mifare Card Readers

### Read Range

KRxxx-E: Up to 10CM

KRxxx-M: Up to 5CM

### Reading Time

≤300ms

### Input Port

External LED Control

External Buzzer Control

### Material

ABS+PC with texture

### Output Format

KRxxx-E: 26bit Wiegand (Default)

KRxxx-M: 34bit Wiegand (Default)

### Power/Current

DC 6-14V / Max.70mA

### LED

Red and Green LEDs

### Operating Temperature

-20°C to 65°C(-10° to +70°C)

### Operating Humidity

10% to 90% relative humidity

non-condensing

### Beeper

Yes

### Index of Protection

KR600-E/M: IP65

KR601-E/M: IP65

KR602-E/M: IP64

## Dimensions

	KR600 E/M	KR601 E/M	KR602 E/M
<b>Height:</b>	11.6cm	8.6cm	8.6cm
<b>Depth:</b>	1.6cm	1.6cm	2cm
<b>Width:</b>	7.5cm	8.6cm	8.6cm

### ZKTeco Inc.

ZK Mansion, Wuhe Rd, Gangtuo, Bantian, Buji Town,  
Longgang District, Shenzhen China 518129

Tel: 86-755-8960 2345/46/47/48

E-mail: sales@zkteco.com

www.zkteco.com

### Global Offices:

USA: +1 732-412-6007

EU: +34 916532891

Brazil: +55 31 2515-8326

Thailand: +66-027199154

Mexico: +52-55-52928418

South Africa: +27 12 259 1047

Egypt: +201110444134

Dubai: +971 4 6091 310

India: +91 8123536788

Indonesia: +62 21 2921 8949

Vietnam : +84-0169-5813007

Philippines: +63 9084118832

Russia: +8 915 178-46-81